Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Cable, UPS Communications Simple Signalling



940-0020

<i>I</i> 1.	-	-		••	
	,,	,	16		Λ,
O١	\sim		.,	_,	•

Lead time Usually in Stock

Main

Number of rack unit	OU	
Cable length	1.8 m	
Number of cables	1	
Product compatibility	UPS	

Physical

Colour	Grey
Net weight	0.45 kg
Mounting mode	Not rack-mountable
Cable end 2	SUB-D 9 male simple signaling
Cable end 1	SUB-D 9 female simple signaling

Output

Number of port

Environmental

Storage Relative Humidity	095 %
Storage altitude	015240 m
Ambient air temperature for operation	045 °C
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-1545 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	22.9 cm
Package 1 Width	5.1 cm
Package 1 Length	10.2 cm

Package 1 Weight 0.45 kg

Contractual warranty

Warranty (in months)

24



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins