

Product datasheet

Specifications



APC Rack Air Removal Unit SX Fan Assembly 100-240V 50/60 Hz

ACF115

⚠ Discontinued on: 31 Oct 2025

⚠ Discontinued

Overview

Lead time Usually in Stock

Main

| | |
|-----------------------|---|
| Main Input Voltage | 100 V 120 V 200 V 208 V 230 V |
| Input Connection Type | IEC 60320 C14 NEMA 5-15P |
| Number of cables | 2 |
| Provided equipment | Installation guide |

General

Air flow 755.1 l/s

Physical

| | |
|---------------------|--------------------|
| Colour | Black |
| Height | 135.3 cm |
| Width | 58.4 cm |
| Depth | 19.1 cm |
| Net weight | 47.27 kg |
| Mounting preference | No preference |
| Mounting mode | Not rack-mountable |

Input

| | |
|-------------------|----------|
| Input power | 1200 W |
| Network frequency | 50/60 Hz |

Conformance

| | |
|------------------------|--|
| Product certifications | cUL listed CE UL listed VDE VCCI |
|------------------------|--|

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|------------------|---|
| Standards | EN 55022 class A EN 55024 FCC part 15 class A ICES-003 IEC 61000-3-2 IEC 61000-3-3 |
|------------------|---|

Environmental

| | |
|--|------------|
| Ambient air temperature for operation | 0...50 °C |
| Ambient air temperature for storage | 0...50 °C |
| Relative humidity | 0...95 % |
| Storage Relative Humidity | 0...95 % |
| Storage altitude | 0...4572 m |
| Acoustic level | 79 dBA |

Communications & Management

| | |
|----------------------|--|
| Control panel | Multifunction LCD status and control console |
|----------------------|--|

Packing Units

| | |
|-------------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 152.4 cm |
| Package 1 Width | 30.5 cm |
| Package 1 Length | 81.3 cm |
| Package 1 Weight | 56.82 kg |

Contractual warranty

| | |
|-----------------------------|----|
| Warranty (in months) | 12 |
|-----------------------------|----|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

| | |
|----------------------------------|-----|
| Total lifecycle Carbon footprint | 199 |
|----------------------------------|-----|

Use Better

Materials and Substances

| | |
|--|----|
| Packaging made with recycled cardboard | No |
|--|----|

| | |
|--------------------------------------|----|
| Packaging without single use plastic | No |
|--------------------------------------|----|

| | |
|-----------------------------------|--|
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
|-----------------------------------|--|


| | |
|------------------|-----------------------------------|
| REACH Regulation | REACH Declaration |
|------------------|-----------------------------------|

Use Again

Repack and remanufacture

| | |
|---------------------------------|---|
| End of life manual availability | End of Life Information |
|---------------------------------|---|

| | |
|-----------|----|
| Take-back | No |
|-----------|----|

| | |
|------------|---|
| WEEE Label |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
|------------|---|