

# Product datasheet

Specifications



## APC 19" Rack LCD Console

AP5719

### Overview

<b>Presentation</b>	1U rack-mountable keyboard, mouse, and LCD console with US English keyboard layout.
<b>Lead time</b>	Usually in Stock

### Main

<b>Main Input Voltage</b>	100 V 240 V
<b>Number of rack unit</b>	1U
<b>Provided equipment</b>	C13-C14 power cord Documentation CD Firmware upgrade cable Installation guide NEMA 5-15 power cord PS2 KVM cable Rack mounting hardware Single user rack mount kit USB cable USB KVM cable

### Physical

<b>Colour</b>	Black
<b>Height</b>	44 mm
<b>Width</b>	482 mm
<b>Depth</b>	665 mm
<b>Net weight</b>	17.4 kg
<b>Mounting location</b>	Front Rear
<b>Mounting preference</b>	No preference
<b>Mounting mode</b>	Rack-mounted
<b>Maximum mounting depth</b>	1049.8 mm
<b>Minimum mounting depth</b>	680 mm

### Input

<b>Network frequency</b>	50/60 Hz
--------------------------	----------

### Conformance

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

<b>Product certifications</b>	C-Tick CE Industry Canada KCC NOM UL listed VCCI class A VDE TAA compliance
-------------------------------	---

<b>Standards</b>	EN 55022 class A EN 55024 EN 60950 FCC part 15 class A IEC 60950
------------------	--

## Environmental

<b>Ambient air temperature for operation</b>	0...40 °C
--	-----------

## Supported Hardware

<b>Display size</b>	19 inch
---------------------	---------

<b>Trackball type</b>	PS/2 touchpad USB mouse
-----------------------	----------------------------

<b>Display type</b>	LCD display
---------------------	-------------

<b>Display power consumption</b>	19 W
----------------------------------	------

<b>Pixel size</b>	0.26
-------------------	------

## Packing Units

<b>Unit Type of Package 1</b>	PCE
-------------------------------	-----

<b>Number of Units in Package 1</b>	1
-------------------------------------	---

<b>Package 1 Height</b>	15.2 cm
-------------------------	---------

<b>Package 1 Width</b>	82.6 cm
------------------------	---------

<b>Package 1 Length</b>	67.3 cm
-------------------------	---------

<b>Package 1 Weight</b>	20.99 kg
-------------------------	----------

## Contractual warranty

<b>Warranty (in months)</b>	24
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint	61
----------------------------------	----

## Use Better

### Materials and Substances

Packaging made with recycled cardboard	No
--	----

Packaging without single use plastic	No
--------------------------------------	----

<a href="#">EU RoHS Directive</a>	Compliant with Exemptions
-----------------------------------	---------------------------

REACH Regulation	<a href="#">REACH Declaration</a>
------------------	-----------------------------------

Halogen-free status	Product contains halogen above thresholds
---------------------	---

### Energy efficiency

Energy Efficiency Optimized	Energy efficient product
-----------------------------	--------------------------

## Use Again

### Repack and remanufacture

End of life manual availability	<a href="#">End of Life Information</a>
---------------------------------	---

Take-back	No
-----------	----

WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
------------	---

Image of product / Alternate images

**Alternative**

---



