

Product datasheet

Specifications



17" Rack LCD Console with Integrated 16 Port Analog KVM Switch

AP5816

Overview

Presentation The Rack LCD Console with Integrated KVM Switch combines the functionality of Rack LCD Console and Analog KVM switches in one convenient package optimizing U space in the rack environment, eliminating cable clutter, and offering a value of two products functionality in one package. Keyboard is a US English keyboard layout.

Lead time Usually in Stock

Main

Main Input Voltage 120 V
240 V

Input Connection Type IEC 60320 C14

Number of rack unit 1U

Cable length 1.82 m

Number of cables 1

Provided equipment USB KVM cable
Single user rack mount kit
PS2 KVM cable
NEMA 5-15 power cord
Installation guide
Firmware upgrade cable
Documentation CD
C13-C14 power cord

Physical

Colour Black

Height 43 mm

Width 483 mm

Depth 614 mm

Net weight 14 kg

Mounting location Front

Mounting preference No preference

Mounting mode Rack-mounted

Maximum mounting depth 1049.8 mm

Minimum mounting depth 680 mm

Input

Network frequency 50/60 Hz

Conformance

Product certifications	cUL listed C-Tick CE Industry Canada KCC UL listed VDE TAA compliance
Standards	EN 60950 FCC part 15 class A IEC 60950

Environmental

Ambient air temperature for operation	0...40 °C
--	-----------

Supported Hardware

Display colour	16 colours
Display size	337.9 (H) x 270.3 (V) 17 inch
Trackball type	PS/2 touchpad USB mouse
Display type	LCD display

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13 cm
Package 1 Width	83 cm
Package 1 Length	66.5 cm
Package 1 Weight	20.14 kg

Contractual warranty

Warranty (in months)	24
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint	49
----------------------------------	----

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
--	----

Packaging without single use plastic	No
--------------------------------------	----

EU RoHS Directive	Compliant with Exemptions
-----------------------------------	---------------------------

REACH Regulation	REACH Declaration
------------------	-----------------------------------

Halogen-free status	Product contains halogen above thresholds
---------------------	---

Energy efficiency

Energy Efficiency Optimized	Energy efficient product
-----------------------------	--------------------------

Use Again

Repack and remanufacture

End of life manual availability	End of Life Information
---------------------------------	---

Take-back	No
-----------	----

WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
------------	---

Image of product / Alternate images

Alternative



