

Product datasheet

Specifications



RACK PDU, BASIC, 0U/1U,
120-240V/15A, 220-240V/10A, (8)
C13



AP6015A

Overview

Lead time Usually in Stock

Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Provided equipment	Installation guide Safety guide

Complementary

Input Voltage	100 V 120 V 200 V 208 V 230 V 240 V
Height	240 mm
Width	44 mm
Output Voltage	100 V 120 V 200 V 208 V 230 V 240 V
Depth	93 mm
Net weight	0.91 kg
Mounting location	Front Rear
Mounting preference	No preference
Input Plug Type	IEC 60320 C14
Mounting mode	Not rack-mountable
Rack units	1U
Mounting position	Horizontal
[In] rated current	12 A
permissible voltage	100...240 V
Max line current	15 A
Input current limits	15 A

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Load capacity	2300 VA
Network frequency	50/60 Hz
Outlet type and quantity	8 IEC 60320 C13

Environment

Product certifications	cUL listed CE EAC IRAM UL listed VDE
------------------------	---

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	28.6 cm
Package 1 Width	13 cm
Package 1 Length	21 cm
Package 1 Weight	1.37 kg

SCC14 10731304327797

Contractual warranty

Warranty (in months)	24
----------------------	----



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint	2101
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACH Regulation	REACH Declaration
Halogen-free status	Product contains halogen above thresholds

Energy efficiency

Energy Efficiency Optimized	Energy efficient product
-----------------------------	--------------------------

Use Again

Repack and remanufacture

End of life manual availability	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

