

Product datasheet

Specifications



APC NetShelter Metered-by-Outlet with Switching Rack PDU, 2G, 0U, 32A, 230V, 21 C13 and 3 C19 outlet

AP8653

Overview

Presentation

APC Metered by Outlet with Switching Rack Power Distribution Units (PDUs) enable advanced, user-customizable power control and individual outlet power metering. Remote outlet level controls allow power on/off functionality for power recycling to reboot locked-up equipment and to avoid unauthorized use of individual outlets. Power sequencing delays allow users to define the order in which to power up or down attached equipment. Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding. Current metering provides real-time remote monitoring of connected loads. Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port, and locking IEC receptacles. User-defined alarms warn of potential circuit overloads before critical IT failures occur. Users can access, configure, and control Switched rack PDUs through secure Web, SNMP, or Telnet Interfaces and is complimented by APC Centralized Management platforms using InfraStruxure Central, Capacity Manager and Change Manager.

Lead time

Usually in Stock

Main

Colour	Black
Product or component type	PDU
PDU type	Metered outlet
Cord length	2.9 m
Number of cables	1
Provided equipment	CAN port terminator Installation guide Rack mounting brackets Safety guide Serial configuration cable

Complementary

Input Voltage	200 V 208 V 230 V
Height	1829 mm
Width	56 mm
Output Voltage	230 V
Depth	51 mm
Net weight	8.23 kg
Mounting location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 32 A 2P + E
Mounting mode	Rack-mounted

Rack units	0U
USB compatible	No
Mounting position	Vertical
permissible voltage	220...240 V
Max line current	32 A
Input current limits	32 A
Load capacity	7400 VA
Network frequency	50/60 Hz
Outlet type and quantity	21 IEC 60320 C13 3 IEC 60320 C19

Environment

Product certifications	VDE
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3
Ambient air temperature for operation	-5...60 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0...15240 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	203.8 cm
Package 1 Width	16.2 cm
Package 1 Length	11.8 cm
Package 1 Weight	10.5 kg

Contractual warranty

Warranty (in months)	24
----------------------	----



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint	3459
----------------------------------	------

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACH Regulation	REACH Declaration
Halogen-free status	Product contains halogen above thresholds

Energy efficiency

Energy Efficiency Optimized	Energy efficient product
-----------------------------	---------------------------------

Use Again

Repack and remanufacture

End of life manual availability	End of Life Information
Removable battery	Yes
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

