

Product datasheet

Specifications



Power Cord, Locking C19 to Rewireable, 3.0m



AP8759

Overview

| | |
|---------------------|---|
| Presentation | Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads. |
|---------------------|---|

| | |
|------------------|------------------|
| Lead time | Usually in Stock |
|------------------|------------------|

Main

| | |
|----------------------------------|------------|
| Product or component type | Power cord |
| Main Output Voltage | 240 V |
| Cable length | 3 m |
| Number of cables | 1 |

Physical

| | |
|----------------------------|--------------------|
| Colour | Black |
| Height | 230 mm |
| Width | 230 mm |
| Depth | 45 mm |
| Net weight | 0.37 kg |
| Mounting preference | No preference |
| Mounting mode | Not rack-mountable |

Input

| | |
|-----------------------------------|--------------------|
| Number of input connectors | 1 hard wire 3-wire |
| Max line current | 16 A |
| Input current limits | 16 A |

Output

| | |
|---------------------------------------|-----------------|
| Max current draw | 16 A |
| Number of power socket outlets | 1 IEC 60320 C19 |
| Power cable length | 3.05 m |

Conformance

| | |
|-------------------------------|-----|
| Product certifications | VDE |
|-------------------------------|-----|

Environmental

| | |
|---------------------------------------|--------------|
| Ambient air temperature for operation | 0...70 °C |
| Relative humidity | 20...80 % |
| Operating altitude | 0...10000 ft |
| Ambient air temperature for storage | -20...70 °C |
| Storage Relative Humidity | 20...80 % |
| Storage altitude | 0...15240 m |

Packing Units

| | |
|------------------------------|----------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 23 cm |
| Package 1 Width | 23 cm |
| Package 1 Length | 4.5 cm |
| Package 1 Weight | 0.37 kg |
| Unit Type of Package 2 | CAR |
| Number of Units in Package 2 | 25 |
| Package 2 Height | 26 cm |
| Package 2 Width | 34 cm |
| Package 2 Length | 57 cm |
| Package 2 Weight | 10 kg |
| Unit Type of Package 3 | PAL |
| Number of Units in Package 3 | 25 |
| Package 3 Height | 143.99 cm |
| Package 3 Width | 100 cm |
| Package 3 Length | 120 cm |
| Package 3 Weight | 10 kg |
| SCC14 | 10731304279829 |

Contractual warranty

| | |
|----------------------|----|
| Warranty (in months) | 24 |
|----------------------|----|



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

| | |
|----------------------------------|----|
| Total lifecycle Carbon footprint | 80 |
|----------------------------------|----|

Use Better

Materials and Substances

| | |
|--|---|
| Packaging made with recycled cardboard | No |
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant |
| SCIP Number | 1cdb2fed-a06f-4574-913d-8df8e70936b2 |
| REACH Regulation | REACH Declaration |
| Halogen-free status | Product contains halogen above thresholds |

Energy efficiency

| | |
|-----------------------------|---------------------------------|
| Energy Efficiency Optimized | Energy efficient product |
|-----------------------------|---------------------------------|

Use Again

Repack and remanufacture

| | |
|---------------------------------|---|
| End of life manual availability | End of Life Information |
| Take-back | No |
| WEEE Label | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |