Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Cable, UPS Communications Smart Signalling (6'/2m - DB-9 to RJ-45)

AP940-0625A

Overview

Lead time Usually in Stock

Main

Cable length	2.00 m
Number of cables	1
Product compatibility	UPS

Physical

•		
Height	5.7 cm	
Width	22.2 cm	
Depth	10.8 cm	
Net weight	0.14 kg	
Mounting mode	Not rack-mountable	
Cable end 2	SUB-D 9 female smart signaling	
Cable end 1	RJ45 male	

Output

Number of port 1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.7 cm
Package 1 Width	10.8 cm
Package 1 Length	22.2 cm
Package 1 Weight	0.14 kg
SCC14	10731304310812



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

⊘ Environmental footprint		
Total lifecycle Carbon footprint	1	

Use Better

⊗ Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
Halogen-free status	Product contains halogen above thresholds

Use Again

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins