Product datasheet

Specifications

APC

Rack PDU,Basic, 1U, 16A, 208&230V, (10)C13 & (2)C19

AP9559

Overview

Lead time	Usually in Stock

Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	2.49 m
Number of cables	1
Provided equipment	User manual Rack mounting brackets

Complementary

Input Voltage	120 V 208 V 230 V
Height	44 mm
Width	447 mm
Output Voltage	120 V 208 V 230 V
Depth	57 mm
Net weight	0.98 kg
Mounting location	Front Rear
Mounting preference	No preference
Input Plug Type	IEC 60320 C20
Mounting mode	Rack-mounted
Rack units	1U
Mounting position	Horizontal
permissible voltage	90…250 V
Max line current	16 A
Input current limits	16 A
Load capacity	3680 VA
Network frequency	50/60 Hz

Outlet type and quantity	10 IEC 60320 C13
	2 IEC 60320 C19

Environment

Product certifications	cUL listed
	CE
	UL listed
	VDE
	Victoria
Ambient air temperature for operation	0…45 °C
Relative humidity	0…95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25…65 °C
Storage Relative Humidity	0…95 %
Storage altitude	0…15240 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.5 cm
Package 1 Width	48.3 cm
Package 1 Length	15.2 cm
Package 1 Weight	2.355 kg

Contractual warranty

Warranty (in months)	24

Life Is On | Schneider Electric

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**2394**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant**
SCIP Number	**1cdb2fed-a06f-4574-913d-8df8e70936b2**
REACh Regulation	**REACh Declaration**
Halogen-free status	**Product contains halogen above thresholds**

Energy efficiency

Energy Efficiency Optimized	**Energy efficient product**

Use Again

Repack and remanufacture

End of life manual availability	**End of Life Information**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**

Image of product / Alternate images

Alternative

Life Is On | Schneider Electric