

Product datasheet

Specifications



Rack PDU, Basic, Zero U, 10A, 230V, (15)C13



AP9568

Overview

Lead time Usually in Stock

Main

Colour Black

Product or component type PDU

PDU type Basic

Cord length 1.98 m

Number of cables 1

Provided equipment Installation guide
Rack mounting brackets
Toolless mounting kit

Complementary

Input Voltage 120 V
200 V
208 V
230 V
240 V

Height 610 mm

Width 44 mm

Output Voltage 208 V
230 V

Depth 44 mm

Net weight 2 kg

Mounting location Side

Mounting preference No preference

Input Plug Type IEC 60320 C14

Mounting mode Rack-mounted

Rack units 0U

Mounting position Vertical

permissible voltage 100...240 V

Input current limits 10 A

Load capacity 2300 VA

Network frequency 50/60 Hz

Outlet type and quantity 15 IEC 60320 C13

Environment

Product certifications	cUL listed CE GOST Queensland Australia UL listed VDE
Ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0...15240 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	64.8 cm
Package 1 Width	17.8 cm
Package 1 Length	15.2 cm
Package 1 Weight	2.724 kg

Contractual warranty

Warranty (in months)	24
-----------------------------	----

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 942

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant

SCIP Number 1cdb2fed-a06f-4574-913d-8df8e70936b2

REACH Regulation [REACH Declaration](#)

Halogen-free status Product contains halogen above thresholds

Energy efficiency

Energy Efficiency Optimized Energy efficient product

Use Again

Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

