

Product datasheet

Specifications



Dry contact, Management Options, Dry Contact I/O Card, monitor external UPS environmental sensors, output relays, and input contacts

AP9613

⚠ Discontinued

⚠ Discontinued on: 7 Nov 2025

Overview

Presentation	UPS management SmartSlot Card with Dry Contact (relay) support to monitor external triggers and initiate actions on external devices.
Lead time	Usually in Stock

Main

Product or component type	Dry contact
Number of rack unit	0U
Provided equipment	User manual USB cable
Range of product	Management Options and Cables

Physical

Colour	Black
Height	3.8 cm
Width	12.1 cm
Depth	11.4 cm
Net weight	0.21 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Conformance

Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3 EN 61000-4-2 EN 61000-4-3 EN 61000-4-4 EN 61000-4-6 FCC part 15 class A
-----------	---

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft

Ambient air temperature for storage	-15...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0...15240 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.700 cm
Package 1 Width	16.500 cm
Package 1 Length	23.400 cm
Package 1 Weight	400.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	6
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	3.181 kg

Contractual warranty

Warranty (in months)	24
----------------------	----



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint	282
----------------------------------	-----

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACH Regulation	REACH Declaration
Halogen-free status	Product contains halogen above thresholds

Energy efficiency

Energy Efficiency Optimized	Energy efficient product
-----------------------------	---------------------------------

Use Again

Repack and remanufacture

End of life manual availability	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins