

Cable, UPS Communications Smart Signalling (15' / 4.5m - DB-9 to DB-9 Serial)

AP9804

Overview

Lead time Usually in Stock

Main

Cable length	4.6 m	
Number of cables	1	
Product compatibility	UPS	

Physical

Colour	Black	
Net weight	0.45 kg	
Mounting location	Front	
Mounting mode	Not rack-mountable	
Cable end 2	SUB-D 9 male smart signaling	
Cable end 1	SUB-D 9 female smart signaling	

Output

Number of port

Environmental

Storage Relative Humidity	095 %
Storage altitude	015240 m
Ambient air temperature for operation	045 °C
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-1545 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	22.9 cm
Package 1 Width	5.1 cm
Package 1 Length	10.2 cm

Package 1 Weight 0.45 kg

Contractual warranty

Warranty (in months)

24



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

⊘ Environmental footprint		
Total lifecycle Carbon footprint	113	

Use Better

Packaging made with recycled cardboard	No	
Packaging without single use plastic	No	
EU RoHS Directive	Compliant	
REACh Regulation	REACh Declaration	

Use Again

○ Repack and remanufacture		
End of life manual availability	End of Life Information	
Take-back	No	
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	