

Product datasheet

Specifications



Cable, UPS Signaling for IBM AS/400 and IBMi (IBM Power Systems)

AP98275

Overview

Lead time	Usually in Stock
-----------	------------------

Physical

Height	3.8 cm
Width	17.8 cm
Depth	15.2 cm
Net weight	0.36 kg
Mounting mode	Not rack-mountable
Cable end 2	SUB-D 9 male simple signaling
Cable end 1	SUB-D 9 male simple signaling

Output

Number of port	1
----------------	---

Environmental

Storage Relative Humidity	0...95 %
Storage altitude	0...15240 m
Ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...50000 ft
Ambient air temperature for storage	-15...45 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.1 cm
Package 1 Width	16.5 cm
Package 1 Length	23.5 cm
Package 1 Weight	0.45 kg

Contractual warranty

Warranty (in months)	24
----------------------	----



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint	113
----------------------------------	-----

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACH Regulation	REACH Declaration
Halogen-free status	Product contains halogen above thresholds

Use Again

Repack and remanufacture

End of life manual availability	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins