Product datasheet

Specifications

APC

Power Cord, C19 to C20, 4.5m

AP9887

Overview

Presentation	Rack PDU power cords for a variety of IT equipment. The output and input connections are C19 to C20. The cord length is 4.5m. The Nominal Output Voltage is 230V.
Lead time	Usually in Stock

Main

Product or component type	Power cord
Main Output Voltage	230 V
Input Connection Type	IEC 60320 C20
Cable length	4.5 m
Number of cables	1

Physical

Colour	Black
Net weight	1.59 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Input

permissible voltage	200…240 V
Input current limits	16 A

Output

Max current draw	16 A
Number of power socket outlets	1 IEC 60320 C19

Conformance

Product certifications	VDE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	57.2 cm
Package 1 Width	11.4 cm

Package 1 Length	47 cm
Package 1 Weight	1.82 kg

Contractual warranty

Warranty (in months)	24

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained 〉

How we assess product sustainability 〉

Environmental footprint

Total lifecycle Carbon footprint	**64**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant**
SCIP Number	**1cdb2fed-a06f-4574-913d-8df8e70936b2**
REACh Regulation	**REACh Declaration**
Halogen-free status	**Product contains halogen above thresholds**

Energy efficiency

Energy Efficiency Optimized	**Energy efficient product**

Use Again

Repack and remanufacture

End of life manual availability	**End of Life Information**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**