

Product datasheet

Specifications



Power Cord, C20 to IEC309 (16A), 2.5m



AP9899

Overview

Presentation	This cable connects an IEC C19 outlet to an IEC 309-16A connector. It can be used as a means to plug in a 16A IEC 309 plug into a Rack PDU with IEC C19 outlets.
Lead time	Usually in Stock

Main

Product or component type	Power cord
Input Connection Type	IEC 60320 C20
Cable length	2.4 m

Physical

Colour	Black
Height	95 mm
Width	292 mm
Depth	95 mm
Net weight	0.5 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Input

Max line current	16 A
Input current limits	16 A

Output

Number of power socket outlets	1 IEC 60309 16 A 2P + E
---------------------------------------	-------------------------

Conformance

Product certifications	VDE
-------------------------------	-----

Environmental

Ambient air temperature for operation	-10...40 °C
Relative humidity	20...80 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	10...30 °C

Storage Relative Humidity	20...80 %
Storage altitude	0...15240 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.2 cm
Package 1 Width	30.5 cm
Package 1 Length	10.2 cm
Package 1 Weight	0.609 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	25.4 cm
Package 2 Width	32.2 cm
Package 2 Length	53.2 cm
Package 2 Weight	6.12 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	10
Package 3 Height	143.99 cm
Package 3 Width	100 cm
Package 3 Length	120 cm
Package 3 Weight	6.12 kg

Contractual warranty

Warranty (in months)	24
----------------------	----

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint

32

Use Better

Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant

SCIP Number

1cdb2fed-a06f-4574-913d-8df8e70936b2

REACH Regulation

[REACH Declaration](#)

Halogen-free status

Product contains halogen above thresholds

Energy efficiency

Energy Efficiency Optimized

Energy efficient product

Use Again

Repack and remanufacture

End of life manual availability

[End of Life Information](#)

Take-back

No

WEEE Label

 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins