



APC Back-UPS, Back-UPS, 350VA/210W, Tower, 230V, 4x IEC C13 Outlets, User Replaceable Battery

BK350EI

Overview

Lead time Usually in Stock

Main	
Main Input Voltage	230 V
Main Output Voltage	230 V
Rated power in W	210 W
rated power in VA	350 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	IEC 60320 C14
output connection type	3 IEC 60320 C13 1 IEC 60320 C13 surge 2 IEC Jumpers
Cable length	1.16 m
Number of cables	2
Battery type	Lead-acid battery
Provided equipment	CD with software Documentation CD Installation manual in japanese Detachable IEC power cord Detachable 1.2 m IEC power cord Telephone cable USB cable Warranty card
Range of product	Back-UPS

Batteries & Runtime

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	6 h
Number of battery replacement quantity	1
Battery voltage	12 V
Battery capacity	7.0 Ah
Battery charger power	14 W rated

Battery power in VAH	116 VAh capacity
	84 VAh runtime
Battery life	46 year(s)
Replacement battery	RBC2 ☐
Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v
Extended runtime	0
General	

Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Colour	Beige
Height	165 mm
Width	91 mm
Depth	284 mm
Net weight	6.32 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Input voltage limits	180266 V
Maximum input current	7 A
Switching current capacity	7 A

Output

Maximum configurable power in W	210 W
Output frequency	4763 Hz sync to mains 50/60 Hz +/- 1 Hz unsynchronised
UPS type	Standby
Maximum configurable power in VA	350 VA
Transfer time	6 ms typical : 10 ms maximum

Conformance

Product certifications	C-Tick CE GOST VDE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient air temperature for operation	040 °C
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-1545 °C
Storage Relative Humidity	095 %
Storage altitude	015240 m
Heat dissipation	19 Btu/h

Communications & Management

Free slots	0
Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Control panel	LED Status display with on line : on battery

Surge Protection and Filtering

Surge energy rate	310 J
Noise suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Number of Units in Package 1 1 Package 1 Height 24.000 cm Package 1 Width 19.000 cm Package 1 Length 41.500 cm Package 1 Weight 6.435 kg Unit Type of Package 2 PAM Number of Units in Package 2 70 Package 2 Height 142.000 cm Package 2 Width 100.000 cm Package 2 Length 120.000 cm Package 2 Weight 492.450 kg	_	
Package 1 Height 24.000 cm Package 1 Width 19.000 cm Package 1 Length 41.500 cm Package 1 Weight 6.435 kg Unit Type of Package 2 PAM Number of Units in Package 2 70 Package 2 Height 142.000 cm Package 2 Width 100.000 cm Package 2 Length 120.000 cm Package 2 Weight 492.450 kg	Unit Type of Package 1	PCE
Package 1 Width 19.000 cm Package 1 Length 41.500 cm Package 1 Weight 6.435 kg Unit Type of Package 2 PAM Number of Units in Package 2 70 Package 2 Height 142.000 cm Package 2 Width 100.000 cm Package 2 Length 120.000 cm Package 2 Weight 492.450 kg	Number of Units in Package 1	1
Package 1 Length 41.500 cm Package 1 Weight 6.435 kg Unit Type of Package 2 PAM Number of Units in Package 2 70 Package 2 Height 142.000 cm Package 2 Width 100.000 cm Package 2 Length 120.000 cm Package 2 Weight 492.450 kg	Package 1 Height	24.000 cm
Package 1 Weight 6.435 kg Unit Type of Package 2 PAM Number of Units in Package 2 70 Package 2 Height 142.000 cm Package 2 Width 100.000 cm Package 2 Length 120.000 cm Package 2 Weight 492.450 kg	Package 1 Width	19.000 cm
Unit Type of Package 2 PAM Number of Units in Package 2 70 Package 2 Height 142.000 cm Package 2 Width 100.000 cm Package 2 Length 120.000 cm Package 2 Weight 492.450 kg	Package 1 Length	41.500 cm
Number of Units in Package 2 70 Package 2 Height 142.000 cm Package 2 Width 100.000 cm Package 2 Length 120.000 cm Package 2 Weight 492.450 kg	Package 1 Weight	6.435 kg
Package 2 Height 142.000 cm Package 2 Width 100.000 cm Package 2 Length 120.000 cm Package 2 Weight 492.450 kg	Unit Type of Package 2	PAM
Package 2 Width 100.000 cm Package 2 Length 120.000 cm Package 2 Weight 492.450 kg	Number of Units in Package 2	70
Package 2 Length 120.000 cm Package 2 Weight 492.450 kg	Package 2 Height	142.000 cm
Package 2 Weight 492.450 kg	Package 2 Width	100.000 cm
· · · · · · · · · · · · · · · ·	Package 2 Length	120.000 cm
SCC14 10731304016349	Package 2 Weight	492.450 kg
	SCC14	10731304016349

Contractual warranty

Warranty (in months)

24 Battery|24 UPS



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint		
Total lifecycle Carbon footprint	229	

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	019b51cf-d7f1-4f06-ac85-1378fc94c7aa
REACh Regulation	REACh Declaration
[⋯] Energy efficiency	
Energy Efficiency Optimized	Energy efficient product

Use Again

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Removable battery	User replaceable
Take-back	Yes
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Product datasheet

BK350EI

Image of product / Alternate images

Alternative





