

Product datasheet

Specifications



APC Easy Rack PDU, Switched, 0U, 1 Phase, 3.7kW, 230V, 16A, 20 x C13 and 4 x C19 outlets, IEC60309 2P+E inlet

EPDU1116S

! To be discontinued

! Discontinued on: 6 June 2025

! To be end-of-service on: 31 Dec 2025

Overview

Lead time Usually in Stock

Main

Colour	Black
Product or component type	PDU
PDU type	Switched
Cord length	2.99 m
Number of cables	1
Provided equipment	Installation guide User manual Vertical mounting brackets

Complementary

Input Voltage	200 V 208 V 230 V
Height	1738 mm
Width	55 mm
Output Voltage	230 V
Depth	62 mm
Net weight	7.3 kg
Mounting location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 16 A 2P + E
Mounting mode	Rack-mounted
Rack units	0U
Mounting position	Vertical
Input current limits	16 A
Load capacity	3680 VA
Network frequency	50/60 Hz

Outlet type and quantity	20 IEC 60320 C13 4 IEC 60320 C19
---------------------------------	-------------------------------------

Environment

Product certifications	CE EAC TÜV
-------------------------------	------------------

Ambient air temperature for operation	-5...45 °C
--	------------

Relative humidity	5...95 %
--------------------------	----------

Operating altitude	0...10000 ft
---------------------------	--------------

Ambient air temperature for storage	-25...65 °C
--	-------------

Storage Relative Humidity	5...95 %
----------------------------------	----------

Storage altitude	0...15240 m
-------------------------	-------------

Packing Units

Unit Type of Package 1	PCE
-------------------------------	-----

Number of Units in Package 1	1
-------------------------------------	---

Package 1 Height	195 cm
-------------------------	--------

Package 1 Width	11 cm
------------------------	-------

Package 1 Length	16 cm
-------------------------	-------

Package 1 Weight	8.5 kg
-------------------------	--------

Contractual warranty

Warranty (in months)	12
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	31346aed-552c-4a16-81d9-e683a383b6da
REACH Regulation	REACH Declaration
 Energy efficiency	
Energy Efficiency Optimized	Energy efficient product

Use Again



 Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

