

Product datasheet

Specifications



APC KVM 2G, Server Module, PS/2 with Virtual Media

KVM-PS2VM

Overview

Lead time Usually in Stock

Main

Product or component type Server

Physical

Height 14 mm

Width 125 mm

Depth 125 mm

Net weight 0.14 kg

Mounting preference No preference

Mounting mode Not rack-mountable

Conformance

Product certifications C-Tick
CE
TAA compliance
VCCI class A

Standards FCC part 15 class A
ICES-003
UL 60950-1

Environmental

Ambient air temperature for operation 0...50 °C

Operating altitude 0...10000 ft

Relative humidity 5...95 %

Ambient air temperature for storage -10...60 °C

Storage altitude 0...3048 m

Storage Relative Humidity 5...95 %

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 4.2 cm

Package 1 Width 12.9 cm

Package 1 Length	12.5 cm
Package 1 Weight	0.18 kg
SCC14	10731304286667

Contractual warranty

Warranty (in months)	24
-----------------------------	----


Environmental Data


Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant

 Energy efficiency	
Energy Efficiency Optimized	Energy efficient product

Use Again



 Repack and remanufacture	
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

