



APC Service Bypass Panel- 230V; 100A; MBB; Hardwire input; (3) 30A Hardwire Output

SBP16KRMI4U

Overview

| Lead time | Usually in Stock | |
|-----------|------------------|--|

Main

| Main Input Voltage | 230 V |
|---------------------------|---|
| Product or component type | Bypass kit |
| Main Output Voltage | 230 V |
| Output connector type | Hard wire 3-wire (H N + E) for 3 zone(s) |
| Number of rack unit | 4U |
| Number of cables | 1 |
| Provided equipment | Installation guide Rack mounting brackets User manual |
| Range of product | Maintenance Bypass Panels |

Physical

| • | |
|---------------------|--------------|
| Colour | Black |
| Height | 178 mm |
| Width | 432 mm |
| Depth | 673 mm |
| Net weight | 21.82 kg |
| Mounting location | Front |
| Mounting preference | Lower |
| Mounting mode | Rack-mounted |

Input

| Network frequency | 50/60 Hz |
|----------------------------|---|
| Number of input connectors | 1 hard wire 3-wire (H N + E) 1 hard wire 4-wire (3P + E) |
| Max line current | 100 A |
| Input current limits | 100 A |
| Load capacity | 20000 VA |
| Power factor | 01 |

Output

| Max current draw | 100 A |
|------------------|-----------------|
| Protection type | Circuit breaker |
| Efficiency | 99 % |

Conformance

| Product certifications | CSA GOST |
|------------------------|---|
| Standards | EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 |
| | EN/IEC 62040-2:2018 |

Environmental

| Ambient air temperature for operation | -2045 °C |
|---------------------------------------|-----------|
| Relative humidity | 095 % |
| Operating altitude | 015000 ft |
| Ambient air temperature for storage | -4065 °C |
| Storage Relative Humidity | 095 % |
| Storage altitude | 015240 m |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|-----------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 30.5 cm |
| Package 1 Width | 61 cm |
| Package 1 Length | 99.1 cm |
| Package 1 Weight | 31.753 kg |
| Unit Type of Package 2 | PAL |
| Number of Units in Package 2 | 8 |
| Package 2 Height | 129.5 cm |
| Package 2 Width | 100 cm |
| Package 2 Length | 120 cm |
| Package 2 Weight | 266.08 kg |

Contractual warranty

Warranty (in months) 2



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

| Packaging made with recycled cardboard | No |
|--|--------------------------------------|
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant |
| SCIP Number | 7a19864b-8bf5-40ac-85e8-7678b0910185 |
| REACh Regulation | REACh Declaration |

Use Again

| ○ Repack and remanufacture | |
|----------------------------|---|
| Take-back | Yes |
| WEEE Label | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Image of product / Alternate images

Alternative

















3 Dec 2025

