

# Product datasheet

Specifications



APC Smart-UPS, Line Interactive,  
3kVA, Tower, 230V, 8x IEC  
C13+2x IEC C19 outlets,  
SmartConnect Port+SmartSlot,  
AVR, LCD

SMT3000IC

## Overview

**Presentation** Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

**Lead time** Usually in Stock

## Main

**Product or component type** Uninterruptible power supply (UPS)

## Complementary

**Communication port type** SmartConnect Ethernet port  
SmartSlot

**Software package** SmartConnect software for remote power monitoring feature availability varies by terms of use

**Mounting mode** Tower

**UPS connectivity** Serial port  
USB port  
SmartConnect port  
Available expansion slot

**Battery type** Lead-acid internal included

## Batteries & Runtime

**Run Time** [View Runtime Graph](#)

**Efficiency** [View Efficiency Graph](#)

**Battery type** Lead-acid battery

**Additional information** Configurable for 220 : 230 or 240 nominal output voltage

**Extended runtime** 1

**Number of battery filled slots** 0

**Number of battery free slots** 0

**Battery recharge time** 3 h

**Number of battery replacement quantity** 1

**Battery life** 3...5 year(s)

**Replacement battery** [RBC55](#)

**Battery charger power** 271 W rated

## General

Provided equipment	USB cable
Number of power module	0
Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	Cloud-enabled monitoring
Redundant	No

## Physical

Number of rack unit	0U
Number of cables	1
Colour	Black
Height	435 mm
Width	197 mm
Depth	544 mm
Net weight	52.5 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes

## Input

Main Input Voltage	230 V AC 1 phase
Other Input Voltage	220 V 240 V
Input Connection Type	IEC 320 C20 Schuko CEE 7 / EU1-16P BS1363A British
Input voltage limits	151...302 V adjustable 160...286 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

## Output

Main Output Voltage	230 V AC 1 phase
Other Output Voltage	220 V 240 V
Rated power in W	2700 W
rated power in VA	3000 VA
output connection type	8 IEC 320 C13 2 IEC Jumpers 1 IEC 320 C19
Harmonic distortion	Less than 5 %
Maximum configurable power in VA	3000 VA

Maximum configurable power in W	2700 W
Transfer time	6 ms typical : 10 ms maximum
UPS type	Line interactive
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

## Conformance

Product certifications	CE EAC RCM VDE UK PSTI
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

Acoustic level	53 dBA
Heat dissipation	375 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0...15240 m
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

## Communications & Management

Control panel	Multifunction LCD status and control console
Emergency power off	Yes
Free slots	1
Communication port support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

## Surge Protection and Filtering

Surge energy rate	365 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	69.901 cm
Package 1 Width	38.100 cm
Package 1 Length	76.200 cm
Package 1 Weight	63.548 kg

# Contractual warranty

---

Warranty (in months)

36 UPS|24 Battery

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint 2891

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number 0637234b-27c7-4e32-ae29-543dd4803a99

REACH Regulation [REACH Declaration](#)

### Energy efficiency

Energy Efficiency Optimized Energy efficient product

## Use Again

### Repack and remanufacture

End of life manual availability [End of Life Information](#)

Removable battery User replaceable

Take-back Yes

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

---

