

Product datasheet

Specifications



APC Smart-UPS On-Line, 5kVA, Rackmount 3U, 230V, 6x C13+4x C19 IEC outlets, Network Card+SmartSlot, Extended runtime, W/ rail kit, Marine

SRT5KRMXLIM

Overview

Presentation	High availability, ruggedized power protection for shipboard and other transportation applications.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V
Product or component type	Uninterruptible power supply (UPS)
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	4500 W
rated power in VA	5000 VA
output connection type	6 IEC 60320 C13 2 IEC Jumpers 4 IEC 60320 C19
Provided equipment	Documentation CD Installation guide Rack mounting hardware Rack mounting brackets Rack mounting support rails Temperature probe Warranty card

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Battery type	Lead-acid battery
Battery voltage	192 V
Extended runtime	1
Number of battery filled slots	0
Battery recharge time	1 h
Number of battery replacement quantity	1
Battery life	3...5 year(s)
Replacement battery	APCRBC140

Battery charger power	837 W rated
-----------------------	-------------

General

Number of power module filled slots	0
-------------------------------------	---

Number of power module free slots	0
-----------------------------------	---

Redundant	No
-----------	----

UPS type	Double conversion online
----------	--------------------------

Physical

Colour	Black
--------	-------

Height	130 mm
--------	--------

Width	432 mm
-------	--------

Depth	719.4 mm
-------	----------

Net weight	54.43 kg
------------	----------

Mounting location	Front
-------------------	-------

Mounting preference	No preference
---------------------	---------------

Mounting mode	Rack-mounted
---------------	--------------

Two post mountable	0
--------------------	---

USB compatible	Yes
----------------	-----

Input

Number of input connectors	1 hard wire 3-wire (1P + N + E)
----------------------------	---------------------------------

Network frequency	45...65 Hz auto-sensing
-------------------	-------------------------

Output

Bypass type	Internal bypass (automatic and manual)
-------------	--

Crest factor	3 : 1
--------------	-------

Harmonic distortion	Less than 3 %
---------------------	---------------

Maximum configurable power in VA	5000 VA
----------------------------------	---------

Maximum configurable power in W	4500 W
---------------------------------	--------

Wave type	Sine wave
-----------	-----------

Output frequency	50/60 Hz +/- 3 Hz sync to mains
------------------	---------------------------------

Conformance

Product certifications	CE DNV EAC RCM VDE
------------------------	--------------------------------

Marking	CE Mark
---------	---------

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
-----------	--

Environmental

Acoustic level	55 dBA
Heat dissipation	931 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0...15240 m
IP degree of protection	IP20
Relative humidity	0...95 % non-condensing
Storage Relative Humidity	0...95 % non-condensing

Communications & Management

Emergency power off	Yes
Free slots	0
Preinstalled device	Dry contact I/O smartslot card
Alarm	Audible and visible alarms : prioritized by severity

Surge Protection and Filtering

Surge energy rate	480 J
-------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	33 cm
Package 1 Width	96 cm
Package 1 Length	61 cm
Package 1 Weight	66.86 kg

Contractual warranty

Warranty (in months)	24 Battery 36 UPS
----------------------	-------------------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint	22168
----------------------------------	-------

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
--	-----

Packaging without single use plastic	No
--------------------------------------	----

EU RoHS Directive	Compliant with Exemptions
-----------------------------------	---------------------------

SCIP Number	4282bd22-a353-4f82-bb5c-97bbd7f1d1e9
-------------	--------------------------------------

REACH Regulation	REACH Declaration
------------------	-----------------------------------

Energy efficiency

Energy Efficiency Optimized	Energy efficient product
-----------------------------	--------------------------

Use Again

Repack and remanufacture

End of life manual availability	End of Life Information
---------------------------------	---

Removable battery	User replaceable
-------------------	------------------

Take-back	No
-----------	----

WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
------------	---

Image of product / Alternate images

Alternative











