

Product datasheet

Specifications



APC Smart-UPS On-Line, 3kVA, Rackmount 3U, 230V, 6x C13+2x C19 IEC outlets, Network Card, Extended runtime, W/ rail kit, W/ Lithium-ion external battery

SRTL3000RMXLI-NC

! Discontinued

! Discontinued on: 24 Sept 2025

Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock


Main

Main Input Voltage	230 V AC 1 phase
Product or component type	Uninterruptible power supply (UPS)
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V 1 phase
Other Output Voltage	220 V 240 V
Rated power in W	2700 W
rated power in VA	3000 VA
Input Connection Type	IEC 60320 C20
output connection type	6 IEC 60320 C13 2 IEC 60320 C19
Number of rack unit	3U
Cable length	1.8 m
Number of cables	1
Provided equipment	CD with software Communication cable Documentation CD Installation guide Removable support feet USB cable Warranty card
Range of product	Smart-UPS On-Line

Complementary

Battery type	Li-Ion (Lithium-Ion) internal included
UPS connectivity	Serial port USB port Pre-installed network management card 3
Mounting mode	Rack-mounted with included kit

Batteries & Runtime

Run Time	View Runtime Graph 
Battery type	Li-Ion (Lithium-Ion)
Battery voltage	48 V
Extended runtime	1
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	4 h
Battery life	5...10 year(s)
Battery charger power	158 W rated

General

Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	Lithium-Ion
Redundant	No
UPS type	Double conversion online

Physical

Colour	Black with silver front bezel
Height	128 mm
Width	432 mm
Depth	639 mm
Net weight	29.2 kg
Mounting preference	No preference
Mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes
Mounting position	Horizontal Vertical

Input

Input voltage limits	160...275 V
Network frequency	40...70 Hz auto-sensing

Output

Bypass type	Built-in bypass
Crest factor	3 : 1
Harmonic distortion	Less than 2 %
Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2700 W
Wave type	Sine wave

Output frequency	50/60 Hz +/- 3 Hz sync to mains
------------------	---------------------------------

Conformance

Product certifications	CE EAC UK PSTI
------------------------	----------------------

Marking	CE Mark
---------	---------

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
-----------	--

Environmental

Acoustic level	50 dBA
----------------	--------

Heat dissipation	780 Btu/h
------------------	-----------

Operating altitude	0...10000 ft
--------------------	--------------

Ambient air temperature for operation	0...40 °C
---------------------------------------	-----------

Ambient air temperature for storage	-20...50 °C
-------------------------------------	-------------

Storage altitude	0...15240 m
------------------	-------------

IP degree of protection	IP20
-------------------------	------

Relative humidity	0...95 % non-condensing
-------------------	-------------------------

Storage Relative Humidity	0...95 % non-condensing
---------------------------	-------------------------

Communications & Management

Emergency power off	Yes
---------------------	-----

Free slots	0
------------	---

Preinstalled device	Network management card 3 with environmental monitoring
---------------------	---

Alarm	Audible and visible alarms : prioritized by severity
-------	--

Surge Protection and Filtering

Surge energy rate	432 J
-------------------	-------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	24.5 cm
------------------	---------

Package 1 Width	87 cm
-----------------	-------

Package 1 Length	60 cm
------------------	-------

Package 1 Weight	41 kg
------------------	-------

Contractual warranty

Warranty (in months)	60
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better





 Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	A64c500c-f72a-458b-8faa-8175a94429fe
REACH Regulation	REACH Declaration
 Energy efficiency	
Energy Efficiency Optimized	Energy efficient product
 Repack and remanufacture	
End of life manual availability	End of Life Information
Removable battery	User replaceable
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative





