

Product datasheet

Specifications

APC



APC SYMMETRA LX 9 BATTERY TOWER XR FRAME, 230V

SYBFXR9I

Overview

| | |
|---------------------|---|
| Presentation | Extended run power protection for servers, networks, and telecommunications |
| Lead time | Usually Ships within 2 Weeks |

Main

| | |
|----------------------------------|-----------------------------------|
| Product or component type | Battery accessory |
| Number of cables | 1 |
| Battery type | Lead-acid battery |
| Provided equipment | Installation guide User manual |
| Range of product | Symmetra Battery Systems |

Batteries & Runtime

| | |
|---|--------------------------|
| Battery location | Battery cabinet |
| Number of battery free slots | 9 |
| Number of battery filled slots | 0 |
| Battery manufacturer | Panasonic |
| Device mounting | Enclosed battery cabinet |
| Battery voltage | 120 V |
| Number of battery replacement quantity | 9 |

Physical

| | |
|----------------------|--------------------|
| Colour | Black |
| Height | 602 mm |
| Width | 483 mm |
| Depth | 726 mm |
| Net weight | 87.27 kg |
| Mounting mode | Not rack-mountable |

Conformance

| | |
|------------------|---|
| Standards | EN 50091-1 EN 50091-2 EN 60950 IEC 60950 |
|------------------|---|

| | |
|-------------------------------|---------------------|
| Product certifications | BSMI VCCI VDE |
|-------------------------------|---------------------|

Environmental

| | |
|---------------------------------------|--------------|
| Ambient air temperature for operation | 0...40 °C |
| Operating altitude | 0...10000 ft |
| Relative humidity | 0...95 % |
| Ambient air temperature for storage | -15...45 °C |
| Storage altitude | 0...4572 m |
| Storage Relative Humidity | 0...95 % |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 91.4 cm |
| Package 1 Width | 99.7 cm |
| Package 1 Length | 59.9 cm |
| Package 1 Weight | 119.09 kg |

Contractual warranty

| | |
|----------------------|----|
| Warranty (in months) | 24 |
|----------------------|----|



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

| | |
|----------------------------------|-----|
| Total lifecycle Carbon footprint | 308 |
|----------------------------------|-----|

Use Better

Materials and Substances

| | |
|--|--|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | No |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| REACH Regulation | REACH Declaration |

Energy efficiency

| | |
|-----------------------------|--------------------------|
| Energy Efficiency Optimized | Energy efficient product |
|-----------------------------|--------------------------|

Use Again

Repack and remanufacture

| | |
|---------------------------------|---|
| End of life manual availability | End of Life Information |
| Removable battery | User replaceable |
| Take-back | Yes |
| WEEE Label | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Image of product / Alternate images

Alternative



