

OM2200 Operations Manager

with Smart Out-of-Band Management



The OM2200 appliance, managed through our Lighthouse software, is configured for data centers and high density locations. Integrated into Opengear's Network Resilience Platform, it provides a separate, secure management plane which supports advanced automation applications.

- 16, 32, 48 Serial port and 24 Serial/24 Ethernet mixed port models
- Separate platforms optimized for 1 GbE and 10 GbE networks
- Global LTE interface (non-cellular optional)
- PSTN modem with select models
- x86 platform; embedded physical security
- Python runtime, Docker container support



Console Specifications

OM2216	16 x RJ45 RS-232 Software Selectable Straight or Rollover Pinout Console Management Ports
OM2232	32 x RJ45 RS-232 Software Selectable Straight or Rollover Pinout Console Management Ports
OM2248	48 x RJ45 RS-232 Software Selectable Straight or Rollover Pinout Console Management Ports
OM2224-24E	24 x Selectable RJ45 RS-232 Ports and 24 x Managed 10/100/1000 Base-T Switched Ethernet Ports

Interfaces

Primary/Secondary Network Ports	2 x 10/100/1000 Ethernet/SFP Fiber auto-media ports (1 GbE chassis) 2 x SFP+ (10G only) Fiber and 1 x 10/100/1000 Base-T Ethernet (10 GbE chassis)
Local Console Ports	1 x micro USB 2.0 Console Port and 1 x RJ45 Serial (Straight Pinout)
Managed Serial Ports	16, 32, or 48 x RJ45 RS-232 Software Selectable 50 to 230,400 bps Console Ports
USB Ports	2 x USB 3.0 Host Ports for storage and 8 x USB 2.0 ports for device console management
Managed Switched Ethernet Ports	24 x managed 10/100/1000 Base-T switched Ethernet Ports (-24E models)

Power Requirements

Dual AC Power Inputs	Dual IEC 60320 Socket Universal 100-240V AC 50/60Hz and IEC C14 side connectors
Dual DC Power Inputs	+/- 40V to 72V DC, 1.5A-0.75A (x2), 48V Nominal
Power Consumption	Serial Port models 1.6 A max Mixed Port models 1.6 A max

Physical Dimensions

Dimensions	17.25 x 10.25 x 1.75 in, 44 x 26 x 4.5 cm
Weight	3.5 kgs 7.7 lbs
Form Factor	1RU

Memory and CPU

CPU	AMD GX-412TC 1.4 Ghz, 4-core 64-bit x86
Memory	8 GB DDR3 RAM
Boot ROM	16 MB SPI with password protection
Internal Storage	M.2 SATA III 64 GB SSD

Environmental

Operating Temperature	5°C to 50°C, 41°F to 122°F
Storage Temperature	-30°C to +60°C, -22°F to +140°F
Humidity	5% to 90%
Cooling	Passive Cooling - can be forward or reverse mounted to suit best airflow

Security, Encryption & Authentication

- Trusted Platform Module 2.0
- AAA - TACACS+, RADIUS, Active Directory/Open LDAP, Kerberos, with local fallback
- Embedded Firewall
- IPSec and OpenVPN

Automation & Scalability

- Opendgear NetOps Modules
- Docker support

Automation & Scalability

- Python
- Perl and bash support
- ZTP
- SNMP-Standard MIBs

Global LTE Cellular Interface

Modules OM22xx-L Sierra Wireless EM7565

Speed CAT12

Coverage Global LTE-A Support

Certifications

Cellular PTCRB, GCF, Verizon and AT&T

Cyber Security EN 18031-1:2024, EN 18031-2:2024, EN 18031-3:2024

Emissions EN55032:2015+A11:2020, EN 61000-3-2:2019, EN 61000-3-3:2013, 47 CFR Parts: 15B, ICES-003 Issue 7

Immunity EN 55035:2017+A11:2020

MTBF 100,000 hours

Other Agency Approvals KS C 9832:2019, KS C 9835:2019, AS/NZ CISPR 32:2015, VCCI-CISPR 32:2016, CISPR 22:2009, CNS 15936:2016

Radio Equipment Directive (RED) EN 301 908-1 V13.1.1, EN 301 908-2 V13.1.1, EN 301 908-13 V13.1.1, EN 303 413 V1.2.1, EN 301 489-1 V2.2.3 (2019-11), EN 301 489-52 V1.1.0

RoHS EN 63000:2018

Safety IEC 60950-1:2005+A1+A2, 62368-1:2023 (Edition 4.0)

Warranty

5 years hardware replacement included. Appliance requires a minimum of 1 year Foundation Support at the time of purchase.

Available Models

Every OM2200 model shares the following features:

- 1 RU form factor
- 1.4 GHz 4-Core x86 CPU
- 8 GB DDR3 RAM

- 64GB Internal Storage
- 2 USB 3.0 and 8 USB 2.0 ports
- RS-232 software selectable straight or rollover pinouts

Model	Managed Ports	Platform	SFP	Cellular	Storage
OM2216	16 Serial Ports	1GbE	2 x 10/100/1000 Ethernet/SFP Fiber Ports	No	64GB
OM2216-L	16 Serial Ports	1GbE	2 x 10/100/1000 Ethernet/SFP Fiber Ports	Global 4G LTE	64GB
OM2232	32 Serial Ports	1GbE	2 x 10/100/1000 Ethernet/SFP Fiber Ports	No	64GB
OM2232-L	32 Serial Ports	1GbE	2 x 10/100/1000 Ethernet/SFP Fiber Ports	Global 4G LTE	64GB
OM2248	48 Serial Ports	1GbE	2 x 10/100/1000 Ethernet/SFP Fiber Ports	No	64GB
OM2248-L	48 Serial Ports	1GbE	2 x 10/100/1000 Ethernet/SFP Fiber Ports	Global 4G LTE	64GB
OM2248-10G	48 Serial Ports	10GbE	2 x SFP+ Fiber and 1 x 10/100/1000 Base-T Ethernet Ports	No	64GB
OM2248-L	48 Serial Ports	10GbE	2 x SFP+ Fiber and 1 x 10/100/1000 Base-T Ethernet Ports	Global 4G LTE	64GB
OM2224-24E	24 Serial Ports + 24 Ethernet Ports	1GbE	2 x 10/100/1000 Ethernet/SFP Fiber Ports	No	64GB
OM2224-24E-L	24 Serial Ports + 24 Ethernet Ports	1GbE	2 x 10/100/1000 Ethernet/SFP Fiber Ports	Global 4G LTE	64GB
OM2224-24E-10G	24 Serial Ports + 24 Ethernet Ports	10GbE	2 x SFP+ Fiber and 1 x 10/100/1000 Base-T Ethernet Ports	No	64GB
OM2224-24E-10G-L	24 Serial Ports + 24 Ethernet Ports	10GbE	2 x SFP+ Fiber and 1 x 10/100/1000 Base-T Ethernet Ports	Global 4G LTE	64GB
OM2224-24E-10G-L -1TB	24 Serial Ports + 24 Ethernet Ports	10GbE	2 x SFP+ Fiber and 1 x 10/100/1000 Base-T Ethernet Ports	Global 4G LTE	1TB

Every appliance ships with 2 x C14 power cables. Country-specific power cables can be purchased separately.

Package Checklist

- Operations Manager OM2200
- 2 x country specific A/C Power Cords
- 1 x Rack Mount Kit (590037)
- 1 x CAT5 Cable 5'
- 1 x DB9F - RJ45 Crossover (319015)
- Start-Up / Safety Instructions Card

Cellular enabled models also include:

- 2 x Cellular Antennas (569041)
- 1 x Cellular Antenna Extender with magnetic base (449041)

Optional Accessories

Part Number	Description
319014	Adapter - DB9F to RJ45 straight serial - DCE -For X2 Pinout
319015	Adapter - DB9F to RJ45 crossover serial - DTE -For X2 Pinout
319016	Adapter - DB9M to RJ45 straight serial - DCE -For X2 Pinout
440016	Cable - Straight through CAT5 - 5' length
590037	Rack Mount Kit - Ears and Screws
449041	Antenna Extender - Magnetic Base with 10' Cable
569041	Antenna - Blade LTE-A with swivel base

Warranty

Part Number	Description
Included	5 year standard warranty

Select one of the following to include with the appliance:

OG-FNTS-OM2200-1YR	1 year Foundation Support for OM2200 - 8x5 Regional Support with Advanced Replacement
OG-FNTS-OM2200-2YR	2 year Foundation Support for OM2200 - 8x5 Regional Support with Advanced Replacement
OG-FNTS-OM2200-3YR	3 year Foundation Support for OM2200 - 8x5 Regional Support with Advanced Replacement
OG-FNTS-OM2200-5YR	5 year Foundation Support for OM2200 - 8x5 Regional Support with Advanced Replacement
OG-FNTS-OM2200-7YR	7 year Foundation Support for OM2200 - 8x5 Regional Support with Advanced Replacement
OG-PRTS-1YR	1 year Premium Support - Access to Premium Resources 24x7 and Advanced

Part Number	Description
	Replacements
OG-PRTS-2YR	2 year Premium Support - Access to Premium Resources 24x7 and Advanced Replacements
OG-PRTS-3YR	3 year Premium Support - Access to Premium Resources 24x7 and Advanced Replacements
OG-PRTS-5YR	5 year Premium Support - Access to Premium Resources 24x7 and Advanced Replacements
OG-PRTS-7YR	7 year Premium Support - Access to Premium Resources 24x7 and Advanced Replacements